

unonovasette  
VARIO COLLECTION



WHEN LIGHT MEETS EMOTIONS



# VARIO 100

SPOTLIGHT OUTDOOR

## TECHNICAL DATA

-  IP66
-  15W / 20W
-  > 90
-  2200K / 2450K / 2700K / 3000K / 4000K
-  10° / 20° / 40° / 55° / 10°x45°
-  Ø94 H120 L94.5mm



## FINISHES



**.01**  
White RAL 9003



**.02**  
Black RAL 9005



**.20**  
Corten



**.23**  
Moss green



# VARIO 60

SPOTLIGHT OUTDOOR

## TECHNICAL DATA

-  IP66
-  6W / 9W / 14W /  
9W RGBW / 12W DW
-  CRI > 90
-  2200K / 2450K / 2700K /  
3000K / 4000K / RGBW / DW
-  10° / 30° / 50° / 10°x45° / 45°x10° /  
35° RGBW / 20° DW / 40° DW
-  Ø62 H87 L112 mm



## FINISHES



**.01**  
White RAL 9003



**.05**  
Black anodized



**.07**  
Natural anodized



**.10**  
Aged solid brass



**.21**  
Pre-aged solid brass



**.23**  
Moss green



Project: Franz Josefs Kai 39, Vienna  
Lighting design: Studio 30 Grad



Project: The BoTree Hotel in Marylebone, London  
Lighting design: dpa lighting consultants

# VARIO 40

SPOTLIGHT OUTDOOR

## TECHNICAL DATA

-  IP66
-  2,6W / 3,6W
-  > 90
-  2200K / 2450K / 2700K / 3000K / 4000K
-  10° / 23° / 43° / 10°x40° / 40°x10°
-  Ø45 H71 L102 mm



## FINISHES



**.01**  
White RAL 9003



**.05**  
Black anodized



**.07**  
Natural anodized



**.10**  
Aged solid brass



**.21**  
Pre-aged solid brass



**.23**  
Moss green



# VARIO 33 ZOOM

SPOTLIGHT OUTDOOR

## TECHNICAL DATA

-  IP66
-  2W
-  > 90
-  2200K / 2700K / 3000K / 4000K
-  6° / 52°
-  Ø33 H70 L74 mm



## FINISHES



**.05**  
Black anodized



**.10**  
Aged solid brass



**.21**  
Pre-aged solid brass



# VARIO 60 P HV

SURFACE MOUNTED  
DOWNLIGHT OUTDOOR

## TECHNICAL DATA

-  IP66
-  9W
- CRI** > 90
- K** 2200K / 2450K / 2700K / 3000K / 4000K
-  10° / 30° / 50° / 10°x45°
-  Ø62 H130 mm



## FINISHES



**.01**

White RAL 9003



**.05**

Black anodized



**.07**

Natural anodized



**.16**

Flamed bronze



**.20**

Corten



**.23**

Moss green

# VARIO 40 P

SURFACE MOUNTED  
DOWNLIGHT OUTDOOR

## TECHNICAL DATA

-  IP66
-  2,6W / 3,6W
- CRI** > 90
- K** 2200K / 2450K / 2700K / 3000K / 4000K
-  10° / 23° / 43° / 10°x40°
-  Ø45 H120 mm





# VARIO 60 S HV

SURFACE MOUNTED  
PENDANT OUTDOOR

## TECHNICAL DATA

-  IP66
-  9W
-  > 90
-  2200K / 2450K / 2700K / 3000K / 4000K
-  10° / 30° / 50° / 10°x45°
-  Body: Ø62 H130 mm  
Ceiling rose: Ø62 H60 mm



# VARIO 40 S

SURFACE MOUNTED  
PENDANT OUTDOOR

## TECHNICAL DATA

-  IP66
-  2,6W / 3,6W
-  > 90
-  2200K / 2450K / 2700K / 3000K / 4000K
-  10° / 23° / 43° / 10°x40°
-  Body: Ø45 H120 mm  
Ceiling rose: Ø62 H60 mm



## FINISHES



.01

White RAL 9003



.05

Black anodized



.07

Natural anodized



.16

Flamed bronze



.20

Corten



.23

Moss green



# VARIO 60 DUO HV

BOLLARD

TECHNICAL DATA

-  IP66
-  10W On/Off  
10W DALI
-  CRI > 90
-  2200K / 2450K / 2700K /  
3000K / 4000K
-  10° / 30° / 50° / 10°x45° / 45°x10°
-  Projector: Ø62 H87 L112 mm  
Bollard: Ø50 H600 / 900 mm



FINISHES



**.05**  
Black anodized



**.20**  
Corten



**.23**  
Moss green



**.27**  
Dune



**.32**  
Warm brown



# VARIO 60 MONO HV

BOLLARD

## TECHNICAL DATA

-  IP66
-  5W On/Off  
5W DALI
-  CRI > 90
-  2200K / 2450K / 2700K /  
3000K / 4000K
-  10° / 30° / 50° / 10°x45° / 45°x10°
-  Projector: Ø62 H87 L112 mm  
Bollard: Ø50 H600 / 900 mm



## FINISHES



**.05**  
Black anodized



**.20**  
Corten



**.23**  
Moss green



**.27**  
Dune



**.32**  
Warm brown





\_CONTEMPORARY DESIGN

\_FLEXIBLE

\_STYLISTIC CONTINUITY

\_HIGH PERFORMANCE

respect the dark

2025\_11